

## Declaration of Conformity

**Identity and address of the browser of the company making the declaration of conformity:**

Mkto Catal Importaciones S.L.

B04267225

Ctra. Huércal-Overa, S/N, 04640, Pulpí, Almería, Spain

**Identity of the object:**

Reference: 20719

Description: 20719, Corvac Thermal Bottle

Materials: Stainless steel, polypropylene (PP) and silicone



**Confirmation of compliance with the applicable regulatory framework:**

Based on the information obtained from our suppliers, this declaration certifies that the article described complies with the stipulations included in Regulations (EC) 1935/2004 on materials and articles intended to come into contact with food, (EU) 10/2011 on plastic materials and articles intended to come into contact with food, relevant requirements of Royal Decree 847/2011 establishing the positive list of substances permitted for the manufacture of polymeric materials intended to come into contact with food and (EC) No. 2023/2006 on good manufacturing practices for materials and articles intended to come into contact with food, in all cases with their subsequent modifications and corrections.

This article complies with the Global Migration Limit (LMG). The tests have been carried out with solutions of 50% ethanol and 3% acetic acid, at 70°C for two hours.

No substances subject to the restrictions set out in Annex I to the Plastics Regulation are used in the manufacture of this object. The object does not release substances in excess of the limit specified in point 1 of Annex II to the Plastics Regulation. Similarly, no primary aromatic amines, referred to in point 2 of Annex II, are released above the detection limit.

**Information on restricted substances in food.**

The subject matter does not include dual-use additives in relation to Regulation (EC) No. 1333/2008 on food additives, or Regulation (EC) No. 1334/2008 on flavourings.

**Specifications on use.**

This object is intended to come into contact with all watery, acidic and alcoholic foods and dairy products. Contact conditions include heating to 70°C for up to 2 hours or heating up to 100°C for up to 15 minutes and not followed by prolonged storage at room temperature or refrigerated. This conformity has been determined by tests where the ratio of the food contact surface to the weight of the food is 10 dm<sup>2</sup>/Kg.

**Description of the functional barrier.**

This item does not contain any plastic layers located behind a functional barrier.

**Signed by and on behalf of:** Mkto Catal Importaciones S.L.

**In Pulpí, 23 de mayo de 2025.**

Mónica López, Product and Certifications Technician

